



Husqvarna DM 230

New, handheld drill motor with attractive design and functional ergonomics. Soft rear section and a larger contact area mean that it sits better against your body. The machine is modular, and therefore easy to maintain and repair.



HANDLE WITH INTEGRATED WATER HOSE

The handle has an integrated water hose, which together with the electric cable run parallel conveniently from the machine.



SMART START®

By pressing the SmartStart button speed is reduced by half, which facilitates to start drilling.



SOFT REAR SECTION

The DM 230 sits comfortable against your body due to the soft rear section and a larger contact area.



THREE GEARS

The DM 230 is equipped with three gears.

Features Husqvarna DM 230

- If the motor runs at too high a load for a long period, it will start to pulsate. If the load is not reduced the motor will shut off, to prevent overheating. Elgard™ significantly increases the machine's service life.
- Functional ergonomics make the Husqvarna drill motors easy and convenient to operate.
- An electronic current limiter for softer starts. Full speed is reached about two seconds after the switch is turned on.
- Equipped with Elgard™ which uses pulsation to indicate when the machine is overloaded. This extends product life.
- When making a starter hole or cutting through reinforcement speed can be reduced by half using SmartStart.
- SoftStart™ – electronic current limiter means full speed is reached about two seconds after start.
- Three-speed water-cooled gearbox for optimal drilling performance and longer service intervals.
- The plastic housing makes it more durable against drops and daily wear.

TECHNICAL SPECIFICATION	
Voltage	230/110V
Amperage	8/15 A
Power	1850 W
Output RPM	700/1700/3600 rpm
Output RPM at full load	500/1400/2900 rpm
Power rating	1100 W
Speeds	3
Water coupling	G 1/4"
Rated output, W	1100/0 W
Rated current, A	8/15 A
Spindle speed idle high speed	900/2150/4500 rpm
Max drill bit diameter, handheld	75 mm
Max drill bit diameter, stand	150 mm
Mounting collar	60 mm
Spindle thread, outer	1 1/4" 7 UNC
Spindle thread, inner	G 1/2" or 5/8" 11 UNC
UNC water coupling	G 1/4"
Weight	7 kg
Sound pressure	90 dB(A)
Sound level	94 dB(A)
Hand arm vibration (Aeq)	2,5 m/s ²



6 - 10 Parkway Drive, Mairangi Bay, Auckland 0632
Ph: 09 443 2436 Auck Ph: 03 341 6923 Chch

www.yrco.co.nz